

**Technical data**

- Special data cable, halogen-free
- **Temperature range**  
flexing +5°C to +70°C  
fixed installation -40°C to +70°C
- **Operating peak voltage**  
(not for heavy current installation purposes)  
0,14 mm<sup>2</sup> = 350 V  
≥ 0,25 mm<sup>2</sup> = 500 V
- **Test voltage**  
0,14 mm<sup>2</sup> = 800 V  
≥ 0,25 mm<sup>2</sup> = 1200 V
- **Insulation resistance**  
min. 2 GOhm x km
- **Capacitance**  
core/core < 70 nF/km
- **Minimum bending radius**  
7,5x cable Ø
- **Radiation resistance**  
up to 100x10<sup>6</sup> cJ/kg (up to 100 Mrad)

**Cable structure**

- Bare copper-conductor, fine-wire to DIN VDE 0812
- Conductor construction:  
0,34 mm<sup>2</sup> = 7x0,25 mm
- Core insulation of PE compound type L/MD to DIN VDE 0819-103 / DIN EN 50290-2-23
- Core identification to DIN 47100, without colour repetition
- Cores twisted in layers with optimal lay-length
- Outer sheath compound type HM2 to DIN VDE 0207 part 24
- Sheath colour grey (RAL 7005)
- with meter marking

**Properties****Tests**

- Halogen-free to DIN VDE 0482 part 267, DIN EN 50267-2-1, IEC 60754-1 (equivalent DIN VDE 0472 part 815)
- Corrosiveness of combustion gases acc.to DIN VDE 0482 part 267, DIN EN 50267-2-2, IEC 60754-2 (equivalent DIN VDE 0472 part 813)
- Halogen-free sheath compound, self-extinguishing and flame retardant acc.to DIN VDE 0482-332-1-2, DIN EN 60332-1-2, IEC 60332-1 (equivalent DIN VDE 0472 part 804 test method B)

**Note**

- AWG sizes are approximate equivalent values. The actual cross-section is in mm<sup>2</sup>.
- screened analogue type:  
**DATAFLAMM®-C**, confer page 145

**Application**

DATAFLAMM® halogen-free data cables are used as connecting cable for signal, measuring, control, call-announcing and two-way intercom speaking systems, clock installations, electronic weighing equipment and electrical apparatus for office requirements. The cables are suitable for installation in dry, damp and wet environments. PE-insulated-cores, compared with the conventional PVC-insulated cores, assure a remarkable and more favourable capacitance values. These cables are generally installed in telecommunication apparatus and data transmission systems in public buildings, laboratories, trading centres where the freedom from halogen in case of fire and the flame propagation must be avoided. The halogen-free thermoplastic sheath produce neither corrosive nor toxic gases.

CE= The product is conformed with the EC Low-Voltage Directive 2006/95/EC.

Part no.	No.cores x cross-sec. mm <sup>2</sup>	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
52300	2 x 0,14	3,3	2,6	14,0	26
52301	3 x 0,14	3,5	4,0	17,0	26
52302	4 x 0,14	3,7	5,3	19,0	26
52303	5 x 0,14	4,0	6,6	23,0	26
52304	6 x 0,14	4,3	7,9	25,0	26
52305	7 x 0,14	4,3	9,2	27,0	26
52306	8 x 0,14	4,6	10,3	30,0	26
52307	10 x 0,14	5,4	13,2	38,0	26
52308	12 x 0,14	5,7	16,0	45,0	26
52309	15 x 0,14	6,1	20,1	57,0	26
52310	18 x 0,14	6,7	23,7	65,0	26
52311	21 x 0,14	7,0	27,9	76,0	26
52312	25 x 0,14	7,8	33,4	88,0	26
52313	30 x 0,14	8,2	39,3	98,0	26
52314	34 x 0,14	8,8	45,5	111,0	26
52315	40 x 0,14	9,5	53,6	139,0	26
52316	50 x 0,14	10,5	64,9	174,0	26
52317	2 x 0,25	3,8	4,7	18,0	24
52318	3 x 0,25	4,0	7,1	21,0	24
52319	4 x 0,25	4,3	9,5	26,0	24
52320	5 x 0,25	4,7	12,0	31,0	24
52321	7 x 0,25	5,1	16,6	40,0	24
52322	10 x 0,25	6,4	24,0	56,0	24
52323	12 x 0,25	6,6	28,6	64,0	24
52324	15 x 0,25	7,4	36,0	80,0	24
52430	18 x 0,25	7,9	43,2	90,0	24
52431	21 x 0,25	8,6	50,4	105,0	24
52325	25 x 0,25	9,4	59,8	121,0	24
52326	34 x 0,25	11,0	81,3	168,0	24
52327	40 x 0,25	12,0	96,0	196,0	24
52328	2 x 0,34	4,4	6,4	25,0	22
52329	3 x 0,34	4,7	9,7	30,0	22

Part no.	No.cores x cross-sec. mm <sup>2</sup>	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
52330	4 x 0,34	5,0	13,0	35,0	22
52331	5 x 0,34	5,5	16,4	43,0	22
52332	7 x 0,34	6,0	22,7	58,0	22
52333	10 x 0,34	7,8	32,4	80,0	22
52334	12 x 0,34	8,0	39,1	91,0	22
52335	15 x 0,34	9,0	49,1	115,0	22
52336	18 x 0,34	9,8	59,1	135,0	22
52337	21 x 0,34	10,4	68,3	154,0	22
52338	25 x 0,34	12,0	81,4	180,0	22
52339	34 x 0,34	13,6	111,1	233,0	22
52340	40 x 0,34	14,8	130,5	272,0	22
52341	2 x 0,5	4,6	9,5	30,0	20
52342	3 x 0,5	4,9	14,2	36,0	20
52343	4 x 0,5	5,3	19,2	43,0	20
52344	5 x 0,5	5,9	24,0	56,0	20
52345	7 x 0,5	6,4	33,7	70,0	20
52346	10 x 0,5	8,3	48,0	101,0	20
52347	12 x 0,5	8,6	57,4	117,0	20
52348	15 x 0,5	9,8	72,0	145,0	20
52349	18 x 0,5	10,5	86,4	171,0	20
52350	21 x 0,5	11,1	101,0	197,0	20
52351	25 x 0,5	12,6	120,0	230,0	20
52352	30 x 0,5	13,3	142,6	269,0	20
52353	34 x 0,5	14,5	163,1	301,0	20
52354	40 x 0,5	15,8	192,0	365,0	20
52355	2 x 0,75	5,2	14,3	40,0	19
52356	3 x 0,75	5,5	21,5	51,0	19
52357	4 x 0,75	6,0	28,6	61,0	19
52358	5 x 0,75	6,7	36,1	76,0	19
52359	7 x 0,75	7,3	50,3	97,0	19
52360	10 x 0,75	9,8	72,0	137,0	19
52361	12 x 0,75	10,0	86,2	167,0	19

Dimensions and specifications may be changed without prior notice. (RB01)