

H05V-K PVC-Single Cores, fine wire stranded



Technical data

- PVC single cores to DIN VDE 0285-525-2-31 / DIN EN 50525-2-31 and IEC 60227-3
- **Temperature range**
flexing -5°C to +70°C
fixed installation -30°C to +80°C
- **Nominal voltage** U_0/U 300/500 V
- **Test voltage** 2000 V
- **Insulation resistance**
min. 10 MOhm x km
- **Minimum bending radius**
fixed installation 4x core Ø
- **Radiation resistance**
up to 80×10^6 cJ/kg (up to 80 Mrad)

Cable structure

- Bare Cu-conductor, to DIN VDE 0295 cl.5, fine-wire, BS 6360 cl.5, IEC 60228 cl.5
- Core insulation of PVC compound type T11 to DIN VDE 0207-363-3 / DIN EN 50363-3 and IEC 60227-3
- Core identification see table below

Properties

- The materials used in manufacture are cadmium-free and contain no silicone and free from substances harmful to the wetting properties of lacquers

Tests

- PVC self-extinguishing and flame retardant acc. to DIN VDE 0482-332-1-2, DIN EN 60332-1-2, IEC 60332-1 (equivalent DIN VDE 0472 part 804 test method B)

Note

- The following colours are recommended: black, white, blue, grey, brown, red, orange, turquoise, violet and pink. Exceptions are the colours green and yellow; these are only permitted if the safety regulations allows. Green is permitted for the identification of luminous decorative chains. All 2-coloured combinations of the abovesingle colours are allowed

Application

These single cores are determined for the installation to the inside of apparatus as well as for the protective laying to the lightings, in dry rooms, in production facilities, switch and distributor boards, in tubes, under and surface mounting of plasters.

CE= The product is conformed with the EC Low-Voltage Directive 2006/95/EC.

H05V-K

Cross-sec. mm ²	Outer Ø min. - max. mm	Cop. weight kg / km	BK	GN-YE	BU	BN	RD	WH	GY	VT	YE	PK	GN	TRANS	D-BU	OG	o.col.	2-col.	U-BU
approx. RAL			9005	-	5015	8003	3000	9003	7001	4005	1021	3015	6018	-	5010	2003	-	-	5002



Coil in cardboard (100m)

Packing

H05V-K coil

Part no.	0,5	0,75	1	29081	29082	29083	29084	29085	29086	29087	29088	29089	29090	29091	29092	29093	29094	29095	29096	26386
Part no.	2,1 - 2,5	2,2 - 2,7	2,4 - 2,8	29097	29098	29099	29100	29101	29102	29103	29104	29105	29106	29107	29108	29109	29110	29111	29112	26387
Part no.				29113	29114	29115	29116	29117	29118	29119	29120	29121	29122	29123	29124	29125	29126	29127	29128	26388
1																				



Spool (with various capacity)

Packing

H05V-K spool

Part no.	0,5	0,75	1	26590	26591	26592	26593	26594	26595	26596	26597	26598	26599	26600	26601	26602	26603	26604	26605	26389
Part no.	2,1 - 2,5	2,2 - 2,7	2,4 - 2,8	26606	26607	26608	26609	26610	26611	26612	26613	26614	26615	26616	26617	26618	26619	26620	26621	26390
Part no.				26622	26623	26624	26625	26626	26627	26628	26629	26630	26631	26632	26633	26634	26635	26636	26637	26391
1																				

Continuation ▶

H05V-K PVC-Single Cores, fine wire stranded**H05V-K**

Cross-sec. mm ²	Outer Ø min. - max. mm	Cop. weight kg / km	BK	GN-YE	BU	BN	RD	WH	GY	VT	YE	PK	GN	TRANS	D-BU	OG	o.col.	2-col.	U-BU
approx. RAL			9005	-	5015	8003	3000	9003	7001	4005	1021	3015	6018	-	5010	2003	-	-	-

**Packing****Barrel (with various capacity)**

H05V-K barrel																			
Part no.			26640	26641	26642	26643	26644	26645	26646	26647	26648	26649	26650	26651	26652	26653	26654	26655	26392
0,5	2,1 - 2,5	4,8																	
Part no.			26656	26657	26658	26659	26660	26661	26662	26663	26664	26665	26666	26667	26668	26669	26670	26671	26393
0,75	2,2 - 2,7	7,2																	
Part no.			26672	26673	26674	26675	26676	26677	26678	26679	26680	26681	26682	26683	26684	26685	26686	26687	26394
1	2,4 - 2,8	9,6																	

Dimensions and specifications may be changed without prior notice. (RK01)



Suitable accessories can be found in Chapter X.

- Core end sleeve - ADI
- Core end sleeve - ADU

Cross-sec. mm ²	Outer Ø min. - max. mm	Cop. weight kg / km	RD/WH	BU/WH	BN/WH	D-BU/WH
----------------------------	------------------------	---------------------	-------	-------	-------	---------

**Packing****Coil in cardboard (100m)**

H05V-K coil			RD/WH	BU/WH	BN/WH	D-BU/WH
Part no.			29370	29375	29380	29394
0,5	2,1 - 2,5	4,8				
Part no.			29371	29376	29381	29395
0,75	2,2 - 2,7	7,2				
Part no.			29372	29377	29382	29396
1	2,4 - 2,8	9,6				

Packing**Coil in cardboard (100m)**

(H)07V-K coil			RD/WH	BU/WH	BN/WH	D-BU/WH
Part no.			29373	29378	29383	29397
1,5	2,8 - 3,4	14,4				
Part no.			29374	29379	29384	29398
2,5	3,4 - 4,1	24,0				
Part no.			29385	29386	29387	29399
4	3,9 - 4,8	38,0				
Part no.			29388	29389	29390	29527
6	4,4 - 5,3	58,0				
Part no.			29391	29392	29393	29528
10	5,7 - 6,8	96,0				

**Packing****Spool (with various capacity)**

H05V-K spool			RD/WH	BU/WH	BN/WH	D-BU/WH
Part no.			29745	29746	29747	29748
0,5	2,1 - 2,5	4,8				
Part no.			29749	29750	29751	29752
0,75	2,2 - 2,7	7,2				
Part no.			29753	29754	29755	29756
1	2,4 - 2,8	9,6				

Packing**Spool (with various capacity)**

(H)07V-K spool			RD/WH	BU/WH	BN/WH	D-BU/WH
Part no.			29757	29758	29759	29760
1,5	2,8 - 3,4	14,4				
Part no.			29761	29762	29763	29764
2,5	3,4 - 4,1	24,0				
Part no.			29765	29766	29767	29768
4	3,9 - 4,8	38,0				
Part no.			29769	29770	29771	29772
6	4,4 - 5,3	58,0				
Part no.			29773	29774	29775	29776
10	5,7 - 6,8	96,0				

**Packing****Barrel (with various capacity)**

H05V-K barrel			RD/WH	BU/WH	BN/WH	D-BU/WH
Part no.			28948	28949	28950	28951
0,5	2,1 - 2,5	4,8				
Part no.			28952	28953	28954	28955
0,75	2,2 - 2,7	7,2				
Part no.			28956	28957	28958	28959
1	2,4 - 2,8	9,6				

Packing**Barrel (with various capacity)**

(H)07V-K barrel			RD/WH	BU/WH	BN/WH	D-BU/WH
Part no.			28960	28961	28962	28963
1,5	2,8 - 3,4	14,4				
Part no.			28964	28965	28966	28967
2,5	3,4 - 4,1	24,0				
Part no.			28968	28969	28970	28971
4	3,9 - 4,8	38,0				
Part no.			28972	28973	28974	28975
6	4,4 - 5,3	58,0				
Part no.			28976	28977	28978	28979
10	5,7 - 6,8	96,0				

Dimensions and specifications may be changed without prior notice.