


Industrial Ethernet

DRAG CHAIN ECO

HELUKAT® 100S

SF/UTP 4 core, Category 5e



Type

Cable structure

Inner conductor diameter:
Core insulation:
Core colours:
Stranding element:
Shielding 1:
Shielding 2:
Total shielding:
Outer sheath material:
Cable external diameter:
Outer sheath colour:

Drag chain applications

SF/UTP 4x1x0.15 mm² (stranded)

Copper, bare (AWG 26/19)
PO
whbl, bl, whor, or
Star quad
-
PETP fleece
Foil + braid
PUR
app. 4,8 mm ± 0,2 mm
Green

Electrical data

Characteristic impedance: 100 Ohm ± 15 ohm at 1 to 100 MHz
Insulation resistance, min.: 5 GOhm x km
Loop resistance: 250 Ohm/km max.
Mutual capacitance: 51 nF/km nom.
Test voltage: 0,5 kV
Relative propagation velocity: 67 %

Typical values

Frequency (MHz)	10	16	62,5	100	155
Attenuation (db/100m)	9,5	12,1	24,8	32,0	41,0
Next (db)	50,0	48,0	38,5	35,3	30,0

Technical data

Weight: app. 30 kg/km
bending radius, repeated: 70 mm
Operating temperature range min.: -40°C
Operating temperature range max.: +80°C
Caloric load, approx. value: 0,37 MJ/m
Copper weight: 17,00 kg/km

Norms

Acc. to ISO/IEC 11801, Acc. to EN 50173, Acc. to EIA/TIA 568-A, Category 5e, Flame-retardant acc. to IEC 60332-1, Halogen-free acc. to 60754-2, Corrosiveness acc. to EN50267-2-3, AWM 20963 (80°C/30V)

Application

HELUKAT® 100S Cat 5e drag chain Eco is designed in use in cable carriers and the recurring loads cause by moving machine components. Thanks to the PU sheath, it also offers excellent resistance to common mineral oils, greases and cooling lubricants.

Part no.

82838, INDUSTRIAL ETHERNET CAT.5e

Dimensions and specifications may be changed without prior notice.