



# BUS Cables

## Profibus SK



Indoor + Outdoor



### Type Cable structure

Inner conductor diameter:  
Core insulation:  
Core colours:  
Stranding element:  
Shielding 1:  
Inner sheath material:  
Shielding 2:  
Total shielding:  
Outer sheath material:  
Cable external diameter:  
Outer sheath colour:

### Fixed installation, indoor 1x2x0.64 mm

Copper, bare (AWG 22/1)  
Foam-skin-PE  
rd, gn  
Double core  
Polyester foil over stranded bundle  
PVC  
Polyester foil, aluminium-lined  
Cu braid, tinned  
PVC  
app. 8,0 mm ± 0,4 mm  
Violet similar to RAL 4001

### Fixed installation, outdoor 1x2x0.64 mm

Copper, bare (AWG 22/1)  
Foam-skin-PE  
rd, gn  
Double core  
Polyester foil over stranded bundle  
PVC  
Polyester foil, aluminium-lined  
Cu braid, tinned  
PE  
app. 8,0 mm ± 0,4 mm  
Black similar to RAL 9005

### Electrical data

Characteristic impedance:  
Conductor resistance, max.:  
Insulation resistance, min.:  
Loop resistance:  
Mutual capacitance:  
Test voltage:  
Attenuation:

150 Ohm ± 10 %  
55 Ohm/km  
1 GOhm x km  
110 Ohm/km max.  
35 nF/km nom.  
1,5 kV  
9,6 kHz < 2,5 dB/km  
38,4 kHz < 4,0 dB/km  
4,0 MHz < 22,0 dB/km  
16,0 MHz < 42,0 dB/km

150 Ohm ± 10 %  
55 Ohm/km  
1 GOhm x km  
110 Ohm/km max.  
35 nF/km nom.  
1,5 kV  
9,6 kHz < 2,5 dB/km  
38,4 kHz < 4,0 dB/km  
4 MHz < 22,0 dB/km  
16 MHz < 42,0 dB/km

### Technical data

Weight:  
bending radius, repeated:  
Operating temperature range min.:  
Operating temperature range max.:  
Caloric load, approx. value:  
Copper weight:

app. 79 kg/km  
120 mm  
-40°C  
+80°C  
1,068 MJ/m  
24,00 kg/km

app. 65 kg/km  
120 mm  
-20°C  
+70°C  
1,451 MJ/m  
24,00 kg/km

### Norms

Applicable standards:

Profibus acc. to DIN 19245 T3 and EN50170  
Flame-retardant acc. to IEC 60332-3  
CMG 75°C or CL3 or AWM 21694 600V  
CSA FT 4

Profibus acc. to DIN 19245 T3 and EN50170  
Halogen-free acc. to 60754-2  
-  
-

### Application

HELUKABEL® Profibus SK Indoor + Outdoor have a special structure for processing with the Fast Connect Stripping Tool from Siemens. The indoor version is used for normal requirements in fixed installation applications in equipment; the Outdoor version is used in open-air applications, i.e. can withstand wind, weather and sun (not for burial directly in the ground).

### Part no.

**81903**, Profibus SK

**81904**, Profibus SK

Dimensions and specifications may be changed without prior notice.

R