


TOPGEBER 512 PUR high flexible Feedback cable for

drag chain according to Siemens, Bosch Rexroth, Lenze and other Standards



Technical data

- Special PUR drag chain feedback cable acc. to UL AWM style 20233 and 20236 and CSA
- **Temperature range**
flexing -30°C to +80°C
fixed installation -40°C to +80°C
- **Nominal voltage**
acc. to Siemens 30 V
acc. to Bosch Rexroth and Lenze 300 V
further details on request
- **A.c. test voltage**, 50 Hz
core/core 2000 V
core/screen 1000 V
- **Mutual capacitance** at 800 Hz
core/core approx. 70 nF/km
core/screen approx. 110 nF/km
- **Insulation resistance**
min. 20 MOhm x km
- **Coupling resistance**
max. 250 Ohm
- **Minimum bending radius**
flexing 10x cable Ø
fixed installation 6x cable Ø

Cable structure

- tinned copper, to
DIN VDE 0295 cl.6, extra fine-wire,
BS 6360 cl.6, IEC 60228 cl.6
- Core insulation of special polypropylene
- Core colours on demand
- Fleece wrapping facilitates sliding
- Overall screening of tinned copper wire braid with tinned drain wire, coverage approx. 85%
- Polyester foil
- Outer sheath of PUR
- Sheath colour green (RAL 6018)
acc. to DESINA® or orange

Properties

- PUR outer sheath, low adhesion, extremely abrasion resistant, halogen-free, resistant to UV-, oil-, hydrolysis and microbial attack
- Special feature: These cables are produced to high quality specifications and conform to the DESINA®-standard
- Due to the high grade special core insulation, the PUR sheath and the highly flexible conductor, these cables are ideally suitable for use in drag chains and provide high functional reliability
- Optimum compliance with requirements for electromagnetic compatibility (EMC) by approx. 85% coverage from the braided screen
- Particularly attractive for export-oriented markets due to UL/CSA approval
- The materials used in manufacture are cadmium-free and contain no silicone and free from substances harmful to the wetting properties of lacquers
- Resistant to cleaning and disinfecting agents acc. to



Note

- For a corresponding motor- and servocables please check chapter **TOPSERV® PUR**
- Encoder cables for static application please check chapter **TOPGEBER 511 PVC**
- Brackets () indicate screen.
- SIEMENS product designations 6FX 8008-... are registered trademarks of Siemens AG and are to be used only for purposes of comparison.
- Bosch Rexroth product designations INK- are registered trademarks of Bosch-Rexroth AG and are to be used only for purposes of comparison.
- DESINA®: Explanation: see introduction.

Application

These low-capacitance incremental encoder cables or position feedback cables transmit the control pulses for positioning and operating characteristics of servomotors. These cables are used as connecting cables for tachos, brakes and pulse generators in applications subjected to heavy mechanical stresses in industrial equipment, machine tools, control and automation equipment. Please observe applicable installation regulations for use in energy supply chains.

EMC = Electromagnetic compatibility

To optimize the EMC features we recommend a large round contact of the copper braiding on both ends.

CE = The product is conformed with the EC Low-Voltage Directive 2006/95/EC.

Continuation ►

TOPGEBER 512 PUR high flexible Feedback cable for

drag chain according to Siemens, Bosch Rexroth, Lenze and other Standards



Part no.	No. cores x cross-sec. mm ²	for system	OEM Part no.	Sheath colour	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
700655	(8 x 2 x 0,18)	Siemens	6FX 8008-1BD11	Green	7,8	54,0	79,0	24
78081	(4 x 2 x 0,34 + 4 x 0,5)	Siemens	6FX 8008-1BD21	Green	9,8	83,0	135,0	21
707400	(3 x (2 x 0,14) + 2 x 0,5)	Siemens	6FX 8008-1BD31	Green	9,0	74,0	119,0	21
700657	(3 x (2 x 0,14) + 4 x 0,14 + 2 x 0,5)	Siemens	6FX 8008-1BD41	Green	8,9	66,0	120,0	26
700540	(3 x (2 x 0,14) + 4 x 0,14 + 4 x 0,25 + 2 x 0,5)	Siemens	6FX 8008-1BD51	Green	9,6	75,0	138,0	-
700654	(4 x 2 x 0,18)	Siemens	6FX 8008-1BD61	Green	6,4	35,0	57,0	-
700653	(2 x 2 x 0,18)	Siemens	6FX 8008-1BD71	Green	5,0	24,0	42,0	-
78079	(12 x 0,22)	Siemens	6FX 8008-1BD81	Green	7,5	65,0	74,0	24
804767	(2 x 2 x 0,2 + 2 x 0,38)	Siemens	6FX 8008-2DC00	Green	7,0	40,0	74,0	-
706333	(5 x 2 x 0,25 + 2 x 0,5)	Berger Lahr	-	Green	8,8	69,0	127,0	24
705413	(3 x 2 x 0,25 + 2 x 0,5)	Elau	-	Green	7,4	43,0	82,0	24
707403	(3 x 2 x 0,25)	B+R	-	Green	6,5	31,0	60,0	24
707404	(5 x 2 x 0,14 + 2 x 0,5)	B+R	-	Green	8,7	48,0	98,0	24
707405	3 x (2 x 0,14) + (2 x 0,5)	Lenze	-	Green	9,8	42,0	98,0	24
707406	4 x (2 x 0,14) + (2 x 1,0)	Lenze	-	Green	11,3	66,0	144,0	24
707407	3 x (2 x 0,14) + (3 x 0,14)	Lenze	-	Green	10,3	41,0	127,0	24
702050	(4 x 2 x 0,25 + 2 x 1,0)	Bosch Rexroth	INK-0209 grün	Green	8,8	64,0	99,0	24
78080	(4 x 2 x 0,25 + 2 x 0,5)	Bosch Rexroth	INK-0448 grün	Green	8,5	51,0	106,0	24
77741	(9 x 0,5)	Bosch Rexroth	INK-0208 grün	Green	8,8	69,0	124,0	20
707738	(4 x 2 x 0,25 + 2 x 1,0)	Bosch Rexroth	INK-0209	Orange	8,8	64,0	99,0	20
707739	(4 x 2 x 0,25 + 2 x 0,5)	Bosch Rexroth	INK-0448	Orange	8,5	51,0	106,0	20
707740	(9 x 0,5)	Bosch Rexroth	INK-0208	Orange	8,8	69,0	124,0	20
707408	(4 x 2 x 0,14 + 4 x 1,0 + (4 x 0,14))	Bosch Rexroth	INK-0532	Orange	9,7	81,0	142,0	20
707418	(3 x (2 x 0,25) + 3 x 0,25 + 2 x 1,0)	Bosch Rexroth	INK-0280	Orange	9,0	84,0	134,7	20
707409	(2 x 2 x 0,25 + 2 x 0,5)	Bosch Rexroth	INK-0750	Orange	7,2	38,0	79,0	20
77743	(3 x (2 x 0,14) + 2 x (1 x 0,5))	Heidenhain	-	Green	8,4	81,0	109,0	-
79513	(4 x 2 x 0,14 + 4 x 0,5)	Heidenhain	-	Green	8,5	52,0	100,0	26
707410	(3 x 2 x 0,14 + 2 x 1,0)	Heidenhain	-	Green	9,1	72,0	132,0	26
700560	(4 x 2 x 0,14 + (4 x 0,14) + 4 x 0,5)	Heidenhain	-	Green	8,3	67,0	104,0	-
77753	(10 x 0,14 + 2 x 0,5)	Heidenhain	-	Green	7,2	43,0	83,0	26
78963	(5 x 2 x 0,14 + 2 x 0,5)	Baumüller	-	Green	9,0	72,0	98,0	26
78828	(3 x 2 x 0,25)	-	-	Green	7,2	55,0	83,0	24
79613	(5 x 2 x 0,38 + 2 x 0,5)	-	-	Green	8,6	69,0	130,0	21
77744	(3 x (2 x 0,14) + 2 x 1,0)	-	-	Green	8,2	71,0	107,0	26
78372	(3 x 2 x 0,14 + 2 x 0,5)	-	-	Green	7,2	35,0	67,0	26
77750	(4 x (2 x 0,25) + 2 x 1,0)	-	-	Green	10,5	93,0	175,0	24
705221	(4 x 2 x 0,25)	-	-	Green	7,5	39,0	88,0	24

Dimensions and specifications may be changed without prior notice. (RN07)



Suitable HELUTEC® Signal and power connectors can be found in our Cable Accessories catalogue.