

VSK-PA screw plug



VSK-PA

The screw plug made of polyamide.

Application

- Plant and machine construction
- Robot construction
- Automation technology
- Vehicle construction and shipbuilding
- Rail technology
- Installation technology
- Control cabinet construction

Material


Polyamide

- halogen-free
- phosphor-free

Technical data

Protection class: IP 54

Temperature range: -40°C up to +100°C



Dimensions

G Thread size
GL Thread length

metric thread

Part no. light grey RAL 7035	Part no. dark grey RAL 7001	Part no. black RAL 9005	Size Metr.	Thread length mm	Unit	Net EUR/100 items at a purchase of		
						up to 100	101 - 500	501 - 1000
94700	94980	94750	M12 x 1,5	6,0	100	o. r.	o. r.	o. r.
94701	94981	94751	M16 x 1,5	7,0	100	o. r.	o. r.	o. r.
94702	94982	94752	M20 x 1,5	7,0	100	o. r.	o. r.	o. r.
94703	94983	94753	M25 x 1,5	10,0	100	o. r.	o. r.	o. r.
94704	94984	94754	M32 x 1,5	11,0	50	o. r.	o. r.	o. r.
94705	94985	94755	M40 x 1,5	13,0	50	o. r.	o. r.	o. r.
94706	94986	94756	M50 x 1,5	14,0	25	o. r.	o. r.	o. r.
94707	94987	94757	M63 x 1,5	15,0	25	o. r.	o. r.	o. r.

PG thread

Part no. light grey RAL 7035	Part no. dark grey RAL 7001	Part no. black RAL 9005	Size PG	Thread length mm	Unit	Net EUR/100 items at a purchase of		
						up to 100	101 - 500	501 - 1000
96595	94970	96997	7	6,0	100	o. r.	o. r.	o. r.
96179	94971	96998	9	6,5	100	o. r.	o. r.	o. r.
96180	94972	96999	11	6,5	100	o. r.	o. r.	o. r.
96181	94973	97000	13,5	6,5	100	o. r.	o. r.	o. r.
96182	94974	97001	16	6,5	100	o. r.	o. r.	o. r.
96183	94975	97002	21	8,0	50	o. r.	o. r.	o. r.
96184	94976	96527	29	8,0	25	o. r.	o. r.	o. r.
96185	94977	97004	36	10,0	25	o. r.	o. r.	o. r.
96960	94978	97005	42	10,0	25	o. r.	o. r.	o. r.
96961	94979	97006	48	12,0	25	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request