

**KM-EMV**


- The counternut with cutting edges for secure fixing of EMC cable glands
- for cutting through painted surfaces to ensure optimum contact with equipotential bonding
- increased vibration resistance

Material

Brass, nickel plated

Technical data

Temperature range: up to +200°C

**Dimensions**

G Thread size inside
SW Spanner size

metric thread - female

Part no.	Size Metr.	Spanner size mm	Unit	
90165	M12 x 1,5	15,0	100	-
90166	M16 x 1,5	19,0	100	-
90167	M20 x 1,5	24,0	100	-
90168	M25 x 1,5	30,0	100	-
90169	M32 x 1,5	36,0	100	-
90170	M40 x 1,5	46,0	50	-
90171	M50 x 1,5	60,0	50	-
90172	M63 x 1,5	70,0	25	-

metric thread - female - KM-EMV-XXL - for large cable diameters

Part no.	Size Metr.	Spanner size mm	Unit	
99875	M72 x 2,0	80,0	1	-
93209	M75 x 1,5	80,0	1	-
98698	M80 x 2,0	95,0	1	-

PG thread - female

Part no.	Size PG	Spanner size mm	Unit	
97243	7	15,0	100	-
97244	9	18,0	100	-
97166	11	21,0	100	-
97167	13,5	23,0	100	-
97168	16	26,0	100	-
97169	21	32,0	100	-
97170	29	41,0	50	-
97171	36	51,0	25	-
97245	42	60,0	25	-
97246	48	64,0	25	-

Dimensions and specifications may be changed without prior notice.