



HELUcond PA6-UL corrugated tubes, polyamide

for heavy duty applications



HELUcond PA6-UL-F/B

Heavy-duty cable protection tube for heavy-duty mechanical applications.

Capacity/100mm NW 16/17: approx. 750 N

Application

- Plant and machine construction
- Robot construction
- Automation technology
- Vehicle construction and shipbuilding
- Rail technology
- Installation technology
- Control cabinet construction

Material

Mod. Polyamide PA 6

Flammability acc. to UL 94: V0

- halogen-free
- cadmium-free

Properties

resistant to a multitude of

- fuels
- mineral oils
- greases
- weak bases
- weak acids

Note

UL recognized / UR
Suitable connection glands:
HELUquick, HSSV.

Technical data

Temperature range: -40°C up to +140°C
Temperature range temporary up to +160°C

fine profile / PA6-UL-F

Part no. grey	Part no. black	trade size mm	Inner Ø mm	Outer Ø mm	Per metres	
920384	920394	7,5	6,4	10,0	50	-
920385	920395	10,0	9,0	13,0	50	-
920386	920396	12,0	11,0	15,8	50	-
920387	920397	17,0	16,6	21,0	50	-
920388	920398	23,0	21,6	28,5	50	-

coarse profile / PA6-UL-B

Part no. grey	Part no. black	trade size mm	Inner Ø mm	Outer Ø mm	Per metres	
920389	920399	16,0	15,3	21,0	50	-
920390	920400	21,0	21,6	28,5	50	-
920391	920401	29,0	27,5	34,5	25	-
920392	920402	36,0	35,0	42,5	25	-
920393	920403	48,0	45,5	54,5	25	-

Dimensions and specifications may be changed without prior notice.