

ADU core end sleeves

non insulated

**ADU**



Non-insulated core end sleeves prevent stripped wires from fanning. The hopper-shaped socket enables them to be pushed easily onto the wires.

Material

Socket: copper

Note

Assignment to cable cross section according to DIN 46228: up to 50mm² to nominal size - over 50mm² no specificatin; Assignment to suitable size possible.

**Dimensions**

L Total length

Part no.	Size mm ²	Length mm	Unit	
91368	0,5	6,0	1000	-
91370	0,5	10,0	1000	-
91371	0,75	6,0	1000	-
91372	0,75	8,0	1000	-
91373	1,0	6,0	1000	-
91374	1,0	10,0	1000	-
91375	1,5	7,0	1000	-
91376	1,5	10,0	1000	-
93096	2,5	7,0	1000	-
93097	2,5	10,0	1000	-
93099	4,0	9,0	1000	-
94000	4,0	12,0	1000	-
94001	6,0	10,0	250	-
94002	6,0	12,0	250	-
94003	6,0	15,0	250	-
94004	10,0	12,0	250	-
94005	10,0	15,0	250	-
94006	10,0	18,0	250	-
94007	16,0	12,0	250	-
94008	16,0	15,0	250	-
94009	16,0	18,0	250	-
94010	25,0	12,0	100	-
94011	25,0	15,0	100	-
94012	25,0	18,0	100	-
94013	25,0	25,0	100	-
94014	25,0	32,0	100	-
94015	35,0	18,0	100	-
94016	35,0	25,0	100	-
94018	35,0	32,0	100	-
94019	50,0	18,0	100	-
94020	50,0	22,0	100	-
94021	70,0	25,0	100	-
94022	70,0	32,0	100	-
91030	95,0	25,0	50	-
91031	95,0	32,0	50	-
96841	120,0	32,0	50	-

Dimensions and specifications may be changed without prior notice.